

# HYDRAULIC MOTORS



SPECIFICATIONS		CARATTERISTICHE		
MODEL	BM-400-F	BM-450-F	BM-500-F	BM-600-F
DISPLACEMENT PER REV. <b>cm<sup>3</sup></b>	<b>401</b>	<b>449</b>	<b>497</b>	<b>609</b>
TEORICAL SPECIF.TORQUE <b>daNm</b>	<b>0.63</b>	<b>0.71</b>	<b>0.79</b>	<b>0.97</b>
CONTINUOUS PRESSURE <b>bar</b>	<b>210</b>	<b>210</b>	<b>210</b>	<b>210</b>
PEAK PRESSURE <b>bar</b>	<b>350</b>	<b>350</b>	<b>350</b>	<b>350</b>
MAX SPEED <b>n/min</b>	<b>420</b>	<b>390</b>	<b>360</b>	<b>320</b>
MAX THEORIC CONTINUOUS POWER <b>KW</b>	<b>58.9</b>	<b>61.3</b>	<b>62.6</b>	<b>68.2</b>
MASS <b>Kg</b>	<b>84</b>	<b>84</b>	<b>84</b>	<b>84</b>

ALL OUR MOTOR CAN BE SUPPLIED COMPLETE OF TACHYMETER / ENCODER CONNECTION

